


# UNI-PAC 14

PTFE with aramid fibre in corners  
reinforced braided packing.



## SERVICE & PROPERTIES:

Uni-Pac 14 is diagonally braided from pure PTFE yarn, reinforced with aramid yarn at the corners, impregnated with PTFE dispersion and lubricated with silicone oil.

Uni-Pac 14 is a high performance multi yarn packing combining the advantages of chemically inert PTFE with those of strong and durable aramid. Multi-purpose packing for valves, rotary and piston pumps.

The Uni-Pac range of high quality performance compression packing's are designed to provide a seal between a moving spindle or shaft and the pressurized housing in which it operates.

Uni-Pac utilizes the most advanced production techniques and materials to ensure a high integrity seal is achieved even in the most demanding of industries. They are typically used on valve, rotary and reciprocating pumps.

## AVAILABILITY:

Uni-Pac packing is available in a range of materials and is supplied in square section from 3mm to 25mm as standard with other sizes available on request. Standard boxes are supplied in 8 metres, with Uni-Pac 7 and Uni-Pac 10 also available in 1 metre handy packs.

## MAIN APPLICATIONS:

**1st Recommendation:**  
Pump, Reciprocating Pump, Mixer.

**2nd Recommendation:**  
Valve.

## TYPICAL PHYSICAL PROPERTIES:

Temperature		-100 °C - 280 °C
Pressure (bar)	Pump	30
	Recipro. Pump	100
	Valve	200
Speed		12 (m/s)
pH Range		2 - 12

As the company's products are used for multiplicity of purposes, and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company.. The Company does not give any warranty that the product will be suitable for the use intended by the customer.