

UNI-PAC 7

Fibreglass impregnated with graphite braided packing.



SERVICE & PROPERTIES:

Made from fiberglass yarn and impregnated with a special composite with high percentage graphite base with a slight addition of lubricant and corrosion inhibitor.

For use in dynamic and general applications. Well suited to a small range of valve and pump duties where the use of non-contaminating packing is not important.

The Uni-Pac range of high quality performance compression packing's are designed to provide a seal between a moving spindle or shaft and the pressurized housing in which it operates.

Uni-Pac utilizes the most advanced production techniques and materials to ensure a high integrity seal is achieved even in the most demanding of industries. They are typically used on valve, rotary and reciprocating pumps.

AVAILABILITY:

Uni-Pac packing is available in a range of materials and is supplied in square section from 3mm to 25mm as standard with other sizes available on request. Standard boxes are supplied in 8 metres, with Uni-Pac 7 and Uni-Pac 2240 also available in 1 metre handy packs.

MAIN APPLICATIONS:

1st Recommendation:

Mixer, Valve.

2nd Recommendation:

Pump, Reciprocating Pump.

TYPICAL PHYSICAL PROPERTIES:

Temperature		590 °C
Pressure (bar)	Pump	10
	Recipro. Pump	70
	Valve	100
Speed		2 (m/s)
pH Range		4 - 11

As the company's products are used for multiplicity of purposes, and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company. The Company does not give any warranty that the product will be suitable for the use intended by the customer.